



Home Tap Water Pre-filter (Manual Double Scraping)

The central water Pre-filter is mainly used to 'capture' the particulate impurities, sediment, rust, floating particles, and other big size pollutants in the water. It is like a 'primary wall' to protect your house appliances and plays a positive role in protecting & extending the terminal water production equipment service lifetime, such as downstream pipes, water purifiers, water heaters, wall-mounted furnaces, washing machines, bathroom showers and so on. The prefilter is flushable and reusable.

NFT-SMD-TQ002Y/W is our Basic Double Scraping product in Brass head design. As an upgraded type, the new generation SMD series also the same with other types of Pre-filter, simply to be installed and indicates when the mesh filter needs cleaning through the housing body. However, not only the sturdy plastic scraping frame clings to the stainless steel mesh and can effectively scrape off impurities by gently twisting, but also silicone scraping strip makes the clean process much more efficient. Some types with different configurations of pressure gauge, pressure control valve, and rotatable head which can effectively adapt to various filtration requirements.


The protection cover (color, position, logo) configurations can be modified to meet your needs.

Features & Advantages

- M & F double thread design, adapt to various pipes (Metal & PPR)
- Transparent body with Colors PP cases covered, Dust and scratch proof
- Rotatable Head & Horizontal Head are available to different pipelines
- Long service lifetime and protection function
- National standard 59 Brass, hot extrusion process, Isolation toxic lead
- Explosion-proof filter housing, temperature resistance up to -30°C
- Upgraded PA material Housing and Food Grade 316L Stainless Steel mesh
- High strength body, Water hammer testing more than 100000 times
- Non-Disposable PTFE gaskets ensure tightness
- Quick connection type drainage port with anti-splash cover

Your Home Water Guard

Technical Parameters

Flushing Prefilter	Item #	Flow Rate T/H	Applicable Feed Water	Applicable Pressure MPa	Temperature °C	Fittings/Inlet & Outlet size Inch	Micron Rating um	Dimension mm
	NFT-SMD-TQ002Y/W	3	Municiple Tap Water	0.1~0.5	5-40	3/4" 1/2"	40	/

Detail Pictures

